

Gutter vacuum specifications - 2022 - Tiger 650SS

Tiger 650SS
stainless vac system



Industrial Vacuums
call: 1 300 822 832



Part	Specifications	Comments
PD bareshaft blower	Ingesol Rand	Carbo Steel rotors
	910 m ³ /h, 580 cfm, 900 mbar, 13 psig, 540mb, 16"Hg	
Blower Filter Size	ACMW4F	
Motor speed	3600 RPM	
Motor Drive Pulley	150 x 3 SPZ	
Blower Pulley	180 x 3 SPZ	
Blower speed	3000 RPM	
Blower design volume	900 m ³ /hr	
Blower design pressure	-50 kPag	
Vacuum relief valve setting	-15 kPag	
Pressure gauge	installed	
Vacuum relief valve	installed	
Filtration	Primary blower filter	
	Secondary twin bag filters	Washable
Tank	304 stainless steel 650 kg reinforced wet dry tank-twin intake ports	
Hose Reel	60 metre capable powder coated steel hose reel - lockable	
Petrol Motor	Vanguard 22 HP with 8.5 litre fuel tank	
Transfer hoses	75 mm transfer hoses from bareshaft blower to capture tank	
Trailer	8x5 tandem 4/2.5/3m	1400kg